

KENWOOD

Listen to the Future



TK-2170/3170

Compact VHF/UHF FM Portable Radios

FleetSync[®]
by KENWOOD

GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 4 W (450-490, 400-430 MHz) Models
- Conventional Zones
- 128 Channels / 128 Zones¹
- Single Priority Scan
- Single & Multi-Zone Scan
- List Scan
- 8 Character Alphanumeric Aliases
- Backlit LCD
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- 4 Front Panel PF keys
- 3 Side PF Keys
- Orange Emergency / AUX Key
- 12-Key DTMF / PF Keypad Models²
- 500 mW Audio Power
- Enhanced Kenwood Audio
- Companded Audio
- VOX Ready
- Voice Inversion Scrambler Built-in
- Encryption / ANI Board Control
- Easy Option Port (20-Pin)
- Emergency Call Features
- Emergency Man-Down Option
- QT / DQT
- Two-Tone Decode³
- Single / Two-Tone Encode³

- Operator Selectable Tone³
- DTMF Encode / Decode⁴
- Special Alert Tone Pattern⁵
- Call Key⁶
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver
- Weather-sealed ACC Connector
- Speaker Mic Options
- Windows[®] Programming & Tuning⁷
- Windows[®] Firmware Uploading⁷
- Field Programming & Tuning
- Wired Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain" **
- IP-54/55 Water & Dust Intrusion*

FleetSync[®]

- PTT ID Digital ANI
- Selective Call & Group Call⁸
- Status Messaging⁸
- Emergency Status
- Caller ID Display⁸
- Short Text Messages⁸
- PC Serial Interface



Keypad model also available.

Options

<ul style="list-style-type: none"> KNB-25A Ni-Cd Battery Pack (1,200mAh) KNB-26N Ni-MH Battery Pack (2,000mAh) KNB-35L Li-ion Battery Pack (7.4V/1950mAh) KBP-5 Battery Case KSC-25 Rapid Charger KSC-30 Charger for KNB-25A and KNB-26N 	<ul style="list-style-type: none"> KRA-22 VHF Low Profile Helical Antenna KRA-23 UHF Low Profile Helical Antenna KRA-26 VHF Helical Antenna KRA-27 UHF Whip Antenna KMC-17 Speaker Microphone 	<ul style="list-style-type: none"> KMC-21 Speaker Microphone KEP-2 Earphone Cord Kit for KMC-17 KHS-22 Head Set KHS-7A Lightweight Single Muff Headset KHS-8BL 2-wire Palm Mic with Earphone (Black) 	<ul style="list-style-type: none"> KHS-9BL 3-wire Lapel Mic with Earphone (Black) KLH-117AD Leather Case KLH-117AD Leather Case for DTMF KLH-140SW Swivel Belt Loop KBH-12 Belt Clip
--	---	--	--

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-2170	TK-3170
GENERAL		
Frequency Range	Type 1 136-174 MHz Type 3 —	450-490 MHz 400-430 MHz
Number of Channels	Zone Max. 128 per Radio Conv. Ch Max. 128 per Zone	
Channel Spacing	Wide/Narrow 25, 30 kHz/12.5, 15 kHz 25 kHz/12.5 kHz	
Battery Voltage	7.5V DC±20%	
Battery Life (5-5-90 duty cycle, during hi-power, battery saver off)	with KNB-25A (1200mAh) Approx. 8 hours with KNB-26N (2000mAh) Approx. 12 hours with KNB-35L (1950mAh) Approx. 11 hours	
Operating Temperature Range*	-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability	±2.5ppm (-22°F ~ +140°F)	
Antenna Impedance	50 Ω	
Channel Frequency Spread	Type 1 38 MHz Type 3 —	40 MHz 30 MHz
Dimensions (W x H x D), Projections not included	Radio Only 2-7/32 x 4-5/16 x 5/8 in. (56 x 109 x 16.6 mm) with KNB-35L 2-7/32 x 4-5/16 x 1-1/4 in. (56 x 109 x 31.7 mm) with KNB-25A/26N 2-7/32 x 4-5/16 x 1-1/2 in. (56 x 109 x 37.9 mm)	
Weight (net)	Radio Only 7.2 oz. (205 g) (includes supplied accessories) with KNB-25A 14.6 oz. (415 g) [with antenna (KRA-22/23) and belt clip (KBH-12)] with KNB-26N 16.0 oz. (455 g) [with antenna (KRA-22/23) and belt clip (KBH-12)] with KNB-35L 12.0 oz. (340 g) [with antenna (KRA-22/23) and belt clip (KBH-12)]	
FCC ID	Type 1 ALH34703110 Type 3 —	ALH34713110 ALH34713130
IC Certification	Type 1 282D-34703110 Type 3 —	282D-34713110 282D-34713130

*+14°F ~ +140°F (-10°C ~ +60°C) when KNB-26N/35L in use

Model	TK-2170	TK-3170
RECEIVER (Measurements made per TIA/EIA-603)		
Sensitivity (12dB SINAD)	Wide 0.25 μV Narrow 0.28 μV	
Selectivity	Wide 70 dB Narrow 65 dB	
Intermodulation Distortion	Wide 65 dB Narrow 60 dB	
Spurious Response	65 dB	
Audio Output (4 Ω Impedance)	500 mW with less than 5% distortion	
TRANSMITTER (Measurements made per TIA/EIA-603)		
RF Output Power	High 5 W Low 1 W	4 W 1 W
Spurious Response	70 dB	
Type of Emission	Wide 16K0F3E Narrow 11K0F3E	
FM HUM & Noise	Wide 45 dB Narrow 43 dB	
Audio Distortion	Less than 5%	

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice. FleetSync® is a registered trademark of Kenwood Corporation in the United States and/or other countries. All other trademarks are property of their respective owners.

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
International Protection Standard				
Dust & Water Protection	IP54/55			

*To meet MIL 810 and IP grade, the 2-pin connector cover has to be connected.

Footnotes from front:

- Conventional Zones: 128 Channels / 128 Zones max. per radio; 128 CH max. per Zone.
- Keypad models only.
- Two-Tone Decode (3 sets x 4 pairs each); Single / Two-Tone Encode (10 tones), Operator Selectable Tone (40 QT.DQT code pairs).
- DTMF Encode: PTT ID, Emergency ANI, Auto-Dial (16 numbers); Manual Encode (keypad models), DTMF Decode: Code Squelch (3-10 digit), Selective Call (9-digit with status) Group Codes A, B, C, D & Wild Card characters) and radio Stun.
- Special Alert Tone Patterns operate for 2-Tone, DTMF, FleetSync® selective call decode.
- Call Key 1 & 2: operates for 2-Tone, DTMF and FleetSync® status encode.
- KPG-101D required: Windows®98/NTI 2000/ Me/XP compatible; English/Spanish screen languages.
- ID List capacity is 100 ID's; Short Text Messages are radio stored & LCD displayed; Status Message List capacity is 50.

KENWOOD

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

